



High Efficiency - Twin Alternating Automatic Water Conditioning Systems



8500 * 9000 * 9100 TWIN ECONOMINDER POWER HEAD - TWIN SERIES

The Water Tec Twin Econominder Power head saves up to 50% in salt or potassium. It uses considerably less water by automatically regenerating only when needed! Utilizes dual pressure tanks for continuous soft water, and it never has a down time during regeneration. Unit can cycle as often as every 90 minutes, if required, with no timers to reset!

8500 * 9000 * 9100 Metered Twin

High Capacity System

For outdoor or indoor installations



8500 * 9000 * 9100 Metered Twin

Compact Space System

Ideal for Town homes, Condominiums or when installation space is limited. Can be installed with overall height of 18 inches.



8500 * 9000 * 9100 Twin

Econominder

These top quality control valves are available in 24V or 110V. The regeneration cycles are automatic and dependable.

8500 * 9100 Valve Body

Valve body and meter module are molded from glass-reinforced Noryl for exceptional strength and durability.

9000 Valve Body

Lead free brass valve control.

Proven Reliability

THOUSANDS are in service in western United States.

Stainless Steel

The outer covering is for U.V protection and algae inhibition on outdoor installations (Optional).

Poly Glass Tanks

Tanks constructed of a high-density polyethylene inner shell, thermal wound with fiberglass. These tanks are totally non-corrosive!

Dual Pressure Tanks

System permits one tank to always be in service during regeneration cycles.

Limited Lifetime Warranty

On pressure tanks and brine tanks. There is a full 3 year warranty on parts.

Locally Manufactured by Water Tec of Tucson Inc.

From only the highest quality components at our facility in TUCSON, ARIZONA.

Over 40 Year Reputation

Of immaculate customer service satisfaction, integrity and quality!

	WATER TEC OF TUCSON 4601 S. 3 RD AVE. TUCSON, AZ 85714 PHONE (520)790-1512 FAX (520)745-0549
	WATER TEC OF PHOENIX PHONE (602)288-1422 FAX (520)745-0549 WATER TEC OF NEVADA PHONE (702)270-0900 FAX (702)270-4350
WEBSITE: www.water-tec.com E-MAIL: questions@water-tec.com AZ ROC# 098794 / 104403 NV ROC# 0055223	

Providing service after the sale since 1967.

8500 * 9000 * 9100 SPECIFICATIONS

MODEL NUMBER	GRAINS CAPACITY	RESIN SIZE	BRINE TANK	SALT LBS. USED PER REGEN. CYCLE	WATER GAL. USED PER REGEN. CYCLE	FLOW RATE
TT 918 8500	32,000	(2) 09X24	11X11X18	2-6 LBS.	18 GAL.	8 GPM
TT 948 9100	64,000	(2) 09X40	18X30	4-12 LBS.	22 GAL.	12 GPM
TT 1054 9000	96,000	(2)10X54	18X40	8-28 LBS.	28 GAL.	15 GPM

SYSTEM INCLUDES BYPASS VALVE (AVAILABLE IN ¾", 1" AND 1¼")

ELECTRICAL RATING (REGENERATING CYCLE MOTOR 24V - 60Hz = 2 WATTS)

WORKING PRESSURE (MINIMUM 40 PSI - MAXIMUM 120 PSI @ 34F - 110F)

**OUR SERVICE TECHNICIANS CAN DELIVER
AND ADD SALT OR POTASSIUM TO YOUR
SYSTEM ON A SCHEDULED ROUTE !**



Ask us about SOFTOUCH™ Sodium - free alternative softener pellets !